



## Husky™ 3" Air Operated Diaphragm Pump

The Husky™ 3300 is a heavy duty 3" pump with large flow paths for fluid transfer applications, including high-viscosity materials.

- Robust fluid section to handle the most abrasive applications
- Modular stall-free air valve design
- Four bolt joint design provides even sealing pressure for leak-free operation
- Externally serviceable pilot valves

The pumps are aluminium with Geolast® seats, balls and diaphragms which makes it the ideal fluid transfer pump for drilling applications.



- Classification: Group II Category 2 GD c IIC T4
- Maximum free-flow delivery . 300 gpm (1135 l/min)
- Maximum fluid working pressure . 125 psi (8.6 bar)
- Maximum size pumpable solids . 1/2" (13mm)

The unit is available for rental or purchase and comes supplied complete with:

- 2 off 3" x 15 Mtr Anti-Static Suction/Discharge Hoses

### Dimensions and Weight:

- (L) 612mm x (W) 478mm x (H) 827mm
- Weight: 68kg

For further information please contact us

Nemesis Equipment Ltd

Tel: +44 (0) 1307 466492

Email: [sales@nemesequipment.com](mailto:sales@nemesequipment.com)

[www.nemesequipment.com](http://www.nemesequipment.com)